Technical data sheet

Flush-mount unit for data technology, type A

Item number: 6119494





Installation unit to accommodate two type A data technology modules, suitable for installation in Rapid 80 device installation trunking systems and ISS service poles. The type A data technology support is suitable for accepting the following data connection modules: AMP TYCO (without dust protection cap): SL Series 110Connect and SL Series Toolless; Brand-Rex: modules with item numbers ending in ...JAKS000CR and ...JAKU002; Nexans: LANmark RJ45 with blue adapter clip, LANmark GG45 with metal clip.

Installation unit, consisting of:

- Mounting support, single, type 71MT1 45
 Data technology support, straight outlet, type DTG-2A, colour: see table
- Cover frame AR45, single, without labelling panel, colour: pure white For installation in Rapid 80 device installation trunking and ISS service poles.

Polycarbonate

Master data


Item number	6119494
Туре	DTE-RW G2A1
Description 1	Inst.unit, data technology
Description 2	f.2 connection modules type A
Manufacturer	OBO
Dimension	84x84x59mm
Colour	Pure white; RAL 9010
Material	Polycarbonate
Smallest sales unit	1
Unit of quantity	Piece
Weight	5 kg
Weight unit	kg/100 pc.
CO2 Footprint (GWP) Cradle-to- Gate	0,4201 kg CO2e / 1 Piece

Technical data sheet

Flush-mount unit for data technology, type A



Item number: 6119494



	cal		

Surface version	Matt
Labelling panel	With labelling panel
Halogen-free	yes
Hinged cover	no
Lamp-wire connector	no
With printed label	no
With dust protection	yes
Mounting type	Device installation duct
Protection rating	IP20
Depth	24.3 mm
Support ring	no
Transparent	no
Use	Modular jack
Strain relief option	no
Combination	Basic element with full cover plate