Technical data sheet PYROPLUG® Shell drill crown insulation



Item number: 7202624



Pipe shell for cable insulation consisting of a one-part, hard pipe sleeve and two soft plugs with a 500 mm diameter. Protect the pipe sleeves and plugs against water in order to guarantee safe foaming in case of fire. Application in interior

FBA-D pipe shells, FBA-DS plug, FBA-M fire protection compound, FBA-D-BS additional kit, wall plate









Permanently elastic, closed-pore foam

Master data


Item number	7202624
Туре	FBA-D100
Description 1	Drill crown insulation
Manufacturer	OBO
Dimension	Ø78x100mm
Colour	Red
Material	Permanently elastic, closed-pore foam
Smallest sales unit	1
Unit of quantity	Piece
Weight	15.5 kg
Weight unit	kg/100 pc.

Technical data sheet PYROPLUG® Shell drill crown insulation



Item number: 7202624

Dimensions				
		Length	100 mm	
il		Width	78 mm	
i i	0	Dimension L	100 mm	
1 !	10		<u>'</u>	
	•			
+ + 1	1			
1 1	7			



160	,	cal (uai	a

Fire protection version	Box body
Shape	Round
For opening, max.	100 mm
For opening, min.	78 mm
Accessories required	ves