Technical data sheet

Device support for CEE installation, system length 165 mm, with CEE

Item number: 7407663





Device support of nominal size 2 with a CEE plug connection 16 A for installation in service outlets and cassettes of nominal size 2, 4, 6 and R7. Device support with protective housing and strain relief. Required minimum installation depth: 190 mm when using a straight connector and 160 mm when an angled connector is used.



St

Steel

FS

Strip galvanized

Master data

Item number	7407663
Туре	GT2 CEE16
Description 1	Mounting box
Description 2	with CEE16
Manufacturer	OBO
Dimension	175x75x128
Material	Steel
Surface	Strip galvanized
Surface standard	DIN EN 10346
Smallest sales unit	1
Unit of quantity	Piece
Weight	69 kg
Weight unit	kg/100 pc.
CO2 Footprint (GWP) Cradle-to- Gate	2,2165 kg CO2e / 1 Piece


Technical data sheet


Device support for CEE installation, system length 165 mm, with CEE





Dimensions





Technical data

Floor plate	no
Seal installation option	no
Suitable for raised floor installation	yes
Suitable for screed-flush closed underfloor ducts	yes
Suitable for screed-covered underfloor ducts	yes
Suitable for cavity floor installation	yes
Suitable for underfloor ducts	yes