Technical data sheet

Installation unit for series-mounted devices, 90 x 210 mm



Item number: 6288336

Installation unit made of sheet steel for installation in the trunking section of device installation trunking of the corresponding system size.

Acceptance of series-mounted devices with a total width of 12 PUs on hat rails. Incl. N and PE rails with screwless terminals. The foldable transparent hood can be locked.



CERK

St

Steel

Р

Powder-coated

Master data

Item number	6288336
Туре	IKR12RW90210
Description 1	Flush-mount unit
Description 2	for modular devices
Manufacturer	OBO
Dimension	115x210x500
Colour	Pure white; RAL 9010
Material	Steel
Surface	Powder-coated
Surface standard	
Smallest sales unit	1
Unit of quantity	Piece
Weight	500 kg
Weight unit	kg/100 pc.
CO2 Footprint (GWP) Cradle-to- Gate	17,7262 kg CO2e / 1 Piece

Technical data sheet

Installation unit for series-mounted devices, 90 x 210 mm



Item number: 6288336

Dimensions		
=======================================	Length	500 mm
	Width	210 mm
	Height	115 mm
500		

Technical data

Extension option	no
Number of units	12
Number of rows	1
Type of cover	Transparent
DIN rail	yes
Suitable for duct depth	90
Halogen-free	yes
Cable entry	yes
With mounting plate	no
Mounting type	Device installation duct
Transparent lid	yes