### **Technical data sheet**

### Cable support trough, 4x, with fastening rail

**Item number: 6006904** 





Cable support brackets for quick and easy routing of cables in areas where common cable support systems cannot be installed due to lack of space. The cable support brackets possess a large load-bearing surface as well as rounded outer edges to protect the cables.

In accordance with DIN VDE 0298-300, a maximum support spacing of 0.8 m should not be exceeded.

 $\epsilon$ 

St

Steel

FT

Hot-dip galvanised

#### Master data

Item number	6006904	
Туре	KTW 100 4 FT	
Description 1	Cable support trough	
Description 2	4-way	
Manufacturer	ОВО	
Dimension	400x200x123	
Colour	zinc	
Material	Steel	
Surface	Hot-dip galvanised	
Surface standard	DIN EN ISO 1461	
Smallest sales unit	1	
Unit of quantity	Piece	
Weight	225 kg	
Weight unit	kg/100 pc.	
CO2 Footprint (GWP) Cradle-to- Gate	6,1569 kg CO2e / 1 Piece	

# **Technical data sheet**

# Cable support trough, 4x, with fastening rail





Dimensions			
	Length	198 mm	
	Width	122 mm	
	Height	400 mm	
	Plate thickness	2 mm	
	Dimension L	400 mm	
Technical data			
	Number of troughs	4 St.	
	Version for	Multiple	
	F in kN per trough	0.5 kN	
	With fastening material	no	
	Adjustable	no	