Technical data sheet

Cable carrier trough, single, for individual routing

Item number: 6006890





Cable support brackets for quick and easy routing of cables in areas where common cable support systems cannot be installed due to lack of space. The cable support brackets possess a large load-bearing surface as well as rounded outer edges to protect the cables.

In accordance with DIN VDE 0298-300, a maximum support spacing of 0.8 m should not be exceeded.



St

Steel

FT

Hot-dip galvanised

Master data


Item number	6006890		
Туре	KTW 100 FT		
Description 1	Cable support trough		
Description 2	for single routing		
Manufacturer	OBO		
Dimension	44x200x113		
Colour	zinc		
Material	Steel		
Surface	Hot-dip galvanised		
Surface standard	DIN EN ISO 1461		
Smallest sales unit	1		
Unit of quantity	Piece		
Weight	48 kg		
Weight unit	kg/100 pc.		
CO2 Footprint (GWP) Cradle-to- Gate	1,2123 kg CO2e / 1 Piece		

Technical data sheet

Cable carrier trough, single, for individual routing



Item number: 6006890



4	198	Height	44 11111
		Plate thickness	2 mm
Technical data			
		Number of troughs	0 St.
		Version for	Single
		F in kN per trough	0.35 kN
		With fastening material	no
		Adjustable	no
			'