


# Technical data sheet

## Add-on tee 110 FT

Item number: 6225950



Add-on tee with welded rung for all cable ladder types of 110 mm side height.  
Connectors should be ordered separately and in the appropriate quantity.



St

Steel

FT

Hot-dip galvanised

### Master data

|                                    |                           |
|------------------------------------|---------------------------|
| Item number                        | 6225950                   |
| Type                               | SLAA 1120 R3 FT           |
| Description 1                      | Add-on tee                |
| Description 2                      | for cable ladder          |
| Manufacturer                       | OBO                       |
| Dimension                          | 110x200                   |
| Colour                             | zinc                      |
| Material                           | Steel                     |
| Surface                            | Hot-dip galvanised        |
| Surface standard                   | DIN EN ISO 1461           |
| Smallest sales unit                | 1                         |
| Unit of quantity                   | Piece                     |
| Weight                             | 524 kg                    |
| Weight unit                        | kg/100 pc.                |
| CO2 Footprint (GWP) Cradle-to-Gate | 14,7016 kg CO2e / 1 Piece |


# Technical data sheet

## Add-on tee 110 FT

Item number: 6225950



### Dimensions



|             |        |
|-------------|--------|
| Width       | 200 mm |
| Height      | 110 mm |
| Dimension B | 200 mm |
| Dimension R | 300 mm |

### Technical data

|                               |                    |
|-------------------------------|--------------------|
| Version of the rungs          | Profile perforated |
| Side rail version             | Flat profile       |
| Connector version             | Without connectors |
| Maintain electrical functions | no                 |
| Rustproof steel, pickled      | no                 |
| Wide-span version             | no                 |
| Rail thickness                | 2 mm               |