


Technical data sheet

90° bend with trapezoidal rung, FT

Item number: 7098898



90° bend for shipbuilding cable ladders, type SL 62, with side height of 40 mm with welded, perforated trapezoidal rungs which open in a downwards direction. Connectors should be ordered separately and in the appropriate quantity.



St

Steel

FT

Hot-dip galvanised

Master data

Item number	7098898
Type	SLB 90 62 300 FT
Description 1	90° bend
Description 2	with trapezoidal rung
Manufacturer	OBO
Dimension	B310mm
Colour	zinc
Material	Steel
Surface	Hot-dip galvanised
Surface standard	DIN EN ISO 1461
Smallest sales unit	1
Unit of quantity	Piece
Weight	336 kg
Weight unit	kg/100 pc.
CO2 Footprint (GWP) Cradle-to-Gate	8,0663 kg CO2e / 1 Piece

90° bend with trapezoidal rung, FT



Technical drawing showing the dimensions of the quarter-circle desk:

- The straight edge length is 9,5x40.
- The radius of the curved section is R250.
- The width of the base is 300.
- The height of the base is 300.
- The depth of the base is 310.
- The thickness of the top surface is 40.
- The height of the base from the floor is 50.

Width	300 mm
Height	40 mm

Bend (angle)	90°
Version of the rungs	Profile perforated
Side rail version	Flat profile
Connector version	Without connectors
Maintain electrical functions	no
Change of direction	Horizontal
Rustproof steel, pickled	no
Hinged	no
Side perforation	no
Wide-span version	no
Rail thickness	5 mm