Technical data sheet

Junction box T60, with knock-out entries

Item number: 2007927





Junction box for the connection of cables and lines indoors and in protected outdoor areas. Square design with knock-out entries to the sides and knock-out entries in the bottom. Suitable for wall and ceiling mounting and on mounting panels. With the option to fasten inside and to mount via the corner domes. With fixed clamping cover. Made from halogen-free and UV-resistant materials.

Junction box according to DIN EN 60670. Flame-resistant to DIN EN 60695/2/11, test temperature 650 °C. Impact resistance IK07 according to DIN EN 50102.

Clear internal dimensions: 100x100x48 mm







Polypropylene















Item number	2007927				
Туре	T 60 M25 RO-LGR				
Description 1	Junction box				
Description 2	M25 entry, red cover				
Manufacturer	OBO				
Dimension	114x114x57				
Colour	Grey / red				
Material	Polypropylene				
Smallest sales unit	5				
Unit of quantity	Piece				
Weight	12.3 kg				
Weight unit	kg/100 pc.				
CO2 Footprint (GWP) Cradle-to- Gate	0,4555 kg CO2e / 1 Piece				

Technical data sheet

Junction box T60, with knock-out entries



Item number: 2007927

Dimensions Length 114 mm Width 114 mm From 114 mm Fro

		ca		

Expandable	yes				
No. of entries	7				
Type of entry	Plug-in seal				
Type of entry	Gland				
Type of housing penetration	Pre-marking				
Measured insulation voltage Vi	500 V				
Equipment	Without				
Cover	Not transparent				
Cover fastening	Screwed				
Entry from rear	yes				
Entries	7 x Ø25				
Explosion-tested version	no				
Flame-resistant	acc. to VDE 0471/DIN 695 Part 2-1, test temperature 650°C				
Shape	Square				
Maintain electrical functions	Without				
For Ex zone	Without				
For Ex zone gas	Without				
For Ex zone dust	Without				
Fibre-glass reinforced	no				
Halogen-free	yes				
Clear internal dimensions	100x100x48 mm				
With screening	no				
with lid	yes				
Mounting type	Wall/ceiling mounting				
Nominal cross-section, min.	6 mm²				
Nominal voltage	500 V				
Sealable	yes				
Protection rating	IP67				
Protection rating IK code	IK07.				
Permitted temperature range, max.	60 °C				
Permitted temperature range, min.	-5 °C				
Transparent lid	no				
Weatherproof	no				