

# Technical data sheet

## Coaxial protection device for 7/16 connection: male/female

Item number: 5093171



Coaxial data protection device

- Basic protection
- Simple mounting (adapter)
- Optimum transmission
- High pulse load capacity
- With 7/16 connector


Application: to protect mobile telephony applications.



### Master data

Item number	5093171
Type	DS-7 16 M/W
Description 1	Data line protection device
Description 2	for HF lines
Manufacturer	OBO
Dimension	170V
Smallest sales unit	1
Unit of quantity	Piece
Weight	35.5 kg
Weight unit	kg/100 pc.
CO2 Footprint (GWP) Cradle-to-Gate	0,0441 kg CO2e / 1 Piece

### Dimensions




# Technical data sheet

Coaxial protection device for 7/16 connection: male/female

Item number: 5093171



## Technical data

	Arrestor monitoring	no
	Number of poles	1
	Insertion loss	≤0,95 dB
	Explosion-tested version	no
	Telecommunications contact	no
	Total discharge current (10/350)	5 kA
	Total discharge current (8/20)	10 kA
	Cut-off frequency	3000 MHz
	Maximum continuous voltage AC	130 V
	Maximum continuous voltage DC	185 V
	Lightning impulse current	2.5 kA
	Insulation resistance	>1 GΩ
	Capacity (wire-wire)	<10 pF
	Capacity (wire-earth)	<20 pF
	Kategorie	Type 1+2 / D1+C2
	Lightning protection zone LPZ	0→2
	Mounting type	Connector/cable adapter
	Nominal load current AC	7 A
	Nominal load current DC	10 A
	Testing standard	IEC 61643-21
	Return loss	≥14 dB
	Shielding connection available	yes
	Screening	Direct
	Protection rating	IP40
	Protection level	<800 V
	Protection level wire-wire	<800 V
	Protection level wire-earth	<800 V
Signalling on device	None	
SPD to IEC 61643-21	Class I+II / D1+C2	
Plug-in system	7/16	
Impulse durability wire-wire	C2: 10 kV / 5 kA (8/20μs)	
Impulse durability wire-earth	C2: 10 kV / 5 kA (8/20μs)	
Permitted temperature range, max.	80 °C	
Permitted temperature range, min.	-40 °C	
Wave resistance	50 Ω	