

Technical data sheet

PV complete block 1500 V DC



Item number: 5094210



Type 2 surge protection for PV plants.

- Surge protection according to IEC 60364-7-712 (VDE 0100-712)
- Arresting capacity of 20 kA per pole and up to 40 kA (8/20)
- Error-resistant Y circuit with status display
- The FS variant possesses a potential-free changeover contact for remote signalling

Application: Surge protective devices for PV systems.



Master data

Item number	5094210
Type	V-PV-T2-1500
Description 1	SurgeController V-PV
Description 2	Y-connection for PV systems
Manufacturer	OBO
Dimension	1500V DC
Colour	Grey
Smallest sales unit	1
Unit of quantity	Piece
Weight	33.8 kg
Weight unit	kg/100 pc.
CO2 Footprint (GWP) Cradle-to-Gate	0,2054 kg CO2e / 1 Piece


Technical data sheet

PV complete block 1500 V DC

Item number: 5094210




Dimensions



Length	65.5 mm
Width	71.2 mm
Height	120 mm

Technical data



Arrester surge current (8/20 μ s) [total]	40 kA
Response time	<25 ns
Blow-out	no
Version for	Y configuration
Pole version	Other
Structural width in division units (division unit, 17.5 mm)	4
Operating temperature, max.	80 °C
Operating temperature, min.	-40 °C
Explosion-tested version	no
Remote signalling	no
Maximum continuous voltage DC	1500 V
Integrated back-up fuse	no
Conductor cross-section, flexible (fine-wire), max.	35 mm ²
Conductor cross-section, flexible (fine-wire), min.	2.5 mm ²
Conductor cross-section, rigid (single-wire/multiwire), max.	35 mm ²
Conductor cross-section, rigid (single-wire/multiwire), min.	2.5 mm ²
Lightning protection zone LPZ	1→2
Max. PV voltage	1500 V
Maximum discharge current (8/20 μ s)	40 kA
Installation type	DIN rail 35 mm
Nominal discharge current (8/20 μ s)	20 kA
Network form	DC
DC network form	yes
IT network form	no
Other network form	no
TN network form	no
TN-C network form	no
TN-C-S network form	no
TN-S network form	no
TT network form	no
OBO_Nominal load current (input/output terminal)	50 A
Testclass, type 1	no


Technical data sheet

PV complete block 1500 V DC



Item number: 5094210

Technical data



Testclass, type 2	yes
Testclass, type 3	no
Protection rating	IP20
Protection level	≤4,5 kV
Signalling on device	Visual
SPD to EN 61643-11	Type 2
SPD to IEC 61643-1	Class II
Permitted temperature range, max.	80 °C
Permitted temperature range, min.	-40 °C