


# Technical data sheet

## Cross-connector for Rd 8–10 x Rd 16

Item number: 5312809



- Meets the requirements of VDE 0185-305-3 (IEC/ EN 62305-3)
- Fit: Rd 8-10 x Rd 16 / FL 30
- Mounted with 4 hexagonal bolts M8 x 25 and 4 hexagonal nuts M8 (F)



**St** Steel

**FT** Hot-dip galvanised

### Master data

Item number	5312809
Type	253 10X16
Description 1	Cross-connectors
Manufacturer	OBO
Dimension	8-10mm
Material	Steel
Surface	Hot-dip galvanised
Surface standard	DIN EN ISO 1461
Smallest sales unit	25
Unit of quantity	Piece
Weight	29.8 kg
Weight unit	kg/100 pc.
CO2 Footprint (GWP) Cradle-to-Gate	0,5427 kg CO2e / 1 Piece


# Technical data sheet

## Cross-connector for Rd 8–10 x Rd 16


Item number: 5312809



### Dimensions



Dimension A	60 mm
Dimension B	60 mm



### Technical data

Type of fastening screw	Hexagonal bolt
Type of connector	Cross-connectors
Lightning current carrying capacity	H/100 kA
Suitable for connection	Round conductor Rd 8-10 / Rd 16
Fit	Rd 8-10 x 16 mm
Intermediate plate	no