

# Technical data sheet

## isFang tripod with side outlet

Item number: 5408902



- Screwless installation of freestanding air-termination rods as well as insulated air-termination rods with 50 mm diameter
- E.g. for internal OBO isCon® conductor
- Roof slope to max. 5 degrees
- Incl. Rd 8–10 crossbar for quick round conductor fastening
- Concrete plinths as well as threaded rods should be ordered separately




**A2** Stainless steel

### Master data

Item number	5408902
Type	isFang 3B-250-A
Description 1	Interception rod stand
Description 2	for isCon conductor, internal
Manufacturer	OBO
Dimension	2,9x2,5m
Material	Stainless steel 1.4301
Smallest sales unit	1
Unit of quantity	Piece
Weight	2500 kg
Weight unit	kg/100 pc.
CO2 Footprint (GWP) Cradle-to-Gate	119,4071 kg CO2e / 1 Piece

### Dimensions



Length	1,450 mm
Width	2,900 mm
Height	2,055 mm
Dimension B	2,900 mm
Dimension d min.	50 mm
Dimension H	2,055 mm
Dimension L	1,450 mm

# Technical data sheet

## isFang tripod with side outlet

Item number: 5408902



### Technical data

Air-termination rod holder	Screwless
Version for	Stand