


Technical data sheet

Mesh cable tray GR-Magic® 55 with barrier strip

Item number: 6006453



Mesh cable tray with shaped connector and welded barrier strips of side height 55 mm.

No additional connection components are required for the mesh cable tray, it is simply interlocked. The grid width is 50 x 100 mm.

Magnetic shield insulation without cover 15 dB, with cover 25 dB.



St Steel

G Electrogalvanized

Master data

| | |
|------------------------------------|----------------------------|
| Item number | 6006453 |
| Type | GRM-T 55 100 G |
| Description 1 | Mesh cable tray GRM |
| Description 2 | with 1 barrier strip |
| Manufacturer | OBO |
| Dimension | 55x100x3000 |
| Colour | zinc |
| Material | Steel |
| Surface | Electrogalvanized |
| Surface standard | EN ISO 19598 / EN ISO 4042 |
| Smallest sales unit | 3 |
| Unit of quantity | Metre |
| Weight | 117.433 kg |
| Weight unit | kg/100 m |
| CO2 Footprint (GWP) Cradle-to-Gate | 2,1772 kg CO2e / 1 Meter |


Technical data sheet

Mesh cable tray GR-Magic® 55 with barrier strip


Item number: 6006453



Dimensions



| | |
|-------------|----------|
| Length | 3,000 mm |
| Width | 100 mm |
| Width | 3.94 in |
| Height | 55 mm |
| Height | 2.17 in |
| Dimension A | 59.5 mm |
| Dimension B | 100 mm |
| Dimension H | 58 mm |



Technical data

| | |
|---|----------------------|
| Connector version | Integrated connector |
| Mounting system fastening type | Floor Ceiling Wall |
| Maintain electrical functions | no |
| Integrated partition | One |
| Usable cross-section | 40 cm ² |
| Usable cross-section | 4000 mm ² |
| Profile shape | U-shaped |
| Rustproof steel, pickled | no |
| Screwless connector | yes |
| Wide-span version | no |
| Load test type according to IEC 61537 | Type II |
| Type of connector, cable support system | Click fastening |

Technical data sheet


Mesh cable tray GR-Magic® 55 with barrier strip

Item number: 6006453



Loads

| | |
|-----------------------------------|-----------|
| Insertable support spacings, min. | 1 m |
| Insertable support spacings, max. | 2 m |
| Support spacing 1.0 m | 0.5 kN/m |
| Support spacing 1.5 m | 0.5 kN/m |
| Support spacing 2.0 m | 0.25 kN/m |



Load diagram, GR-Magic mesh cable tray, type GRM-1T 55

- 1 Permitted cable tray/ladder load in kN/m without man load
- 2 Support width in m
- 3 Rail bend in mm at permitted kN/m
- 4 Load scheme during testing
- Load curve with cable tray/ladder width in mm
- Strut bend curve according to support width