

# Technical data sheet

## Flat angle cover, trunking type WDK 15030

Item number: 6158595



Flat angle hood for changing the direction of the WDK trunking.



**PVC** Polyvinylchloride

### Master data

|                                    |                          |
|------------------------------------|--------------------------|
| Item number                        | 6158595                  |
| Type                               | WDK HF15030GR            |
| Description 1                      | Flat angle cover         |
| Manufacturer                       | OBO                      |
| Dimension                          | 15x30mm                  |
| Colour                             | Stone grey; RAL 7030     |
| Material                           | Polyvinylchloride        |
| Smallest sales unit                | 4                        |
| Unit of quantity                   | Piece                    |
| Weight                             | 0.965 kg                 |
| Weight unit                        | kg/100 pc.               |
| CO2 Footprint (GWP) Cradle-to-Gate | 0,0602 kg CO2e / 1 Piece |

# Technical data sheet

Flat angle cover, trunking type WDK 15030

Item number: 6158595



## Dimensions



|             |         |
|-------------|---------|
| Length      | 53 mm   |
| Width       | 30 mm   |
| Height      | 17.5 mm |
| Dimension a | 53 mm   |
| Dimension H | 30 mm   |

## Technical data

|  |              |
|--|--------------|
| Version for                                      | Hood fitting |
| Fastening type                                   | Lockable     |
| Maintain electrical functions for duct dimension | no           |
| Halogen-free                                     | no           |
| Trunking depth                                   | 15 mm        |
| Protection rating                                | IP30         |
| Protective film                                  | no           |
| Protection rating IK code                        | IK04         |
| Permitted temperature range, max.                | 60 °C        |
| Permitted temperature range, min.                | -5 °C        |
| Angle range, max.                                | 90 mm        |
| Angle range, min.                                | 90 mm        |