

Technical data sheet

T piece, for cable trunking type LKM 40060

Item number: 6247733



T piece including cover for changing the direction of the LKM ducts.
Equipotential bonding without additional aids, between base and cover



- St** Steel
- FS** Strip galvanized

Master data

| | |
|------------------------------------|--------------------------|
| Item number | 6247733 |
| Type | LKM T40060FS |
| Description 1 | T piece |
| Description 2 | with cover |
| Manufacturer | OBO |
| Dimension | 40x60mm |
| Colour | zinc |
| Material | Steel |
| Surface | Strip galvanized |
| Surface standard | DIN EN 10346 |
| Smallest sales unit | 1 |
| Unit of quantity | Piece |
| Weight | 46.8 kg |
| Weight unit | kg/100 pc. |
| CO2 Footprint (GWP) Cradle-to-Gate | 1,8144 kg CO2e / 1 Piece |

Technical data sheet

T piece, for cable trunking type LKM 40060

Item number: 6247733



Dimensions

| | |
|-------------|--------|
| Length | 300 mm |
| Width | 60 mm |
| Height | 44 mm |
| Dimension a | 300 mm |



Technical data

| | |
|-----------------------------------|------------------|
| Departing width | 60 mm |
| Departing height | 44 mm |
| Version for | Base and cover |
| Fastening type | Base perforation |
| Maintain electrical functions | no |
| for duct dimension | 40 x 60 |
| Halogen-free | yes |
| Duct height, min. | 44 mm |
| Trunking depth | 44 mm |
| Protection rating | IP30 |
| Protective film | no |
| Protection rating IK code | IK10 |
| Permitted temperature range, max. | 90 °C |
| Permitted temperature range, min. | -5 °C |