

Technical data sheet

Ceramic terminal, single

Item number: 7205702



High-temperature-resistant ceramic terminal for refitting of the FireBox T series.
Tested according to DIN EN 60998-2-1:2004.



Steatit

Master data

Item number	7205702
Type	TK 06
Description 1	Ceramic terminal
Description 2	for FireBox T
Manufacturer	OBO
Dimension	6 mm ²
Colour	Cream
Material	Steatit
Smallest sales unit	5
Unit of quantity	Piece
Weight	0.88 kg
Weight unit	kg/100 pc.
CO2 Footprint (GWP) Cradle-to-Gate	0,0022 kg CO2e / 1 Piece


Technical data sheet

Ceramic terminal, single

Item number: 7205702



Dimensions



Length	8.5 mm
Width	21.5 mm
Height	21.5 mm

Technical data

Closing plate required	no
Connectable conductor cross-section, single-wire, max.	6 mm ²
Connectable conductor cross-section, single-wire, min.	1.5 mm ²
Connection position	Side
No. of terminals	2
Number of screwless terminals per pole	2
Version of electrical connection 1	Screw connection
Version of electrical connection 2	Screw connection
Explosion-tested version	no
Insulation material	Ceramic
Mounting type	Miscellaneous
Nominal cross-section, max.	6 mm ²
Nominal cross-section, min.	1.5 mm ²
Nominal voltage	400 V
Nominal current	41 A
Pole number	1
Permitted temperature range, max.	250 °C
Permitted temperature range, min.	0 °C
Transparent	no