

# Technical data sheet

## UTC4 W with 2 protective contact sockets, orange

Item number: 7404613



The ready-for-connection UTC4 universal support has 2 pre-installed 33° protective contact sockets of 16 A and 2 blanking covers for reinstallation of 2 installation devices of the Modul 45 series. Suitable for VL connection cables and device installation units of nominal size R7, R9 and 9.

PVC connection cable with connector, 3-pin, type WINSTA® MIDI.  
The ready-for-connection UTC4 universal support has 2 pre-installed 33° protective contact sockets of 16 A and 2 blanking covers for reinstallation of 2 installation devices of the Modul 45 series.

PVC connection cable with connector, 3-pin, type WINSTA® MIDI

**PA** Polyamide

### Master data

Item number	7404613
Type	UTC4 W OR2
Description 1	Universal supportConnectWINSTA
Description 2	double orange
Manufacturer	OBO
Dimension	208x76x45
Material	Polyamide
Smallest sales unit	1
Unit of quantity	Piece
Weight	30.7 kg
Weight unit	kg/100 pc.
CO2 Footprint (GWP) Cradle-to-Gate	1,0084 kg CO2e / 1 Piece


# Technical data sheet

UTC4 W with 2 protective contact sockets, orange

Item number: 7404613



## Dimensions



Length	218 mm
Width	76 mm
Height	60 mm

## Technical data

Connection cable, halogen-free	no
Number of installable devices	4
Version for	Double pure orange
Cable length	300 mm
Line cross-section	2.5 mm <sup>2</sup>
Plug-in system	WINSTA® MIDI
Plug connector system, system-specific	yes
Circuit	1
System length	208 mm
Surge protection	no