

Technical data sheet

UTC4 W with 4 protective contact sockets, orange

Item number: 7404614



The ready-for-connection UTC4 universal support possesses 4 pre-installed 33° protective contact sockets in orange, 250 V~, 16 A. Suitable for VL connection cables and device installation units of nominal size R7, R9 and 9.



PVC connection cable with connector, 3-pin, type WINSTA® MIDI.
The ready-for-connection UTC4 universal support has 4 pre-installed 33° protective contact sockets in orange, 250 V~ 16 A.

PVC connection cable with connector, 3-pin, type WINSTA® MIDI

PA Polyamide

Master data

Item number	7404614
Type	UTC4 W OR4
Description 1	Universal supportConnectWINSTA
Description 2	4-way orange
Manufacturer	OBO
Dimension	208x76x45
Material	Polyamide
Smallest sales unit	1
Unit of quantity	Piece
Weight	37.8 kg
Weight unit	kg/100 pc.
CO2 Footprint (GWP) Cradle-to-Gate	1,1951 kg CO2e / 1 Piece



Technical data sheet

UTC4 W with 4 protective contact sockets, orange

Item number: 7404614



Dimensions



Length	218 mm
Width	76 mm
Height	60 mm

Technical data

Connection cable, halogen-free	no
Number of installable devices	4
Version for	4x pure orange
Cable length	300 mm
Line cross-section	2.5 mm ²
Plug-in system	WINSTA® MIDI
Plug connector system, system-specific	yes
Circuit	1
System length	208 mm
Surge protection	no