


Technical data sheet

Support bracket AS 15

Item no. 6421334



Light-duty support bracket for infinitely adjustable fastening on IS 8 support.

The support bracket can be fastened to both sides of the I support.

The necessary clamping lug (item no. 6419015), including bolt and nut can be ordered individually for bracket widths 110–160 mm.




St Steel

FT Hot-dip galvanised

Master data

Item no.	6421334
Type	AS 15 16 FT
Description 1	Support bracket
Description 2	for IS 8 support
Dimension	B160mm
Material	Steel
Material symbol	St
Surface	Hot-dip galvanised
Surface to DIN	DIN EN ISO 1461
Surface symbol	FT
Smallest sales unit (VG)	1 Piece
Weight	32,80 kg/100 pc.

Technical data



Length	160,00 mm
Width	160,00 mm
Side height	55,00 mm
Dimension B	160,00 mm
Dimension H	55,00 mm
Dimension L	160,00 mm
Dimension value	160 x 55
Version	Support bracket
Version	Support bracket
EPD article	☒
F in kN	1,50 kN
Suitable for maintaining electrical function	☐
Rustproof steel, pickled	☐


Technical data sheet

Support bracket AS 15

Item no. 6421334



Load charts



Load diagram, bracket type AS 15

- 1 Bending of the bracket tip at permitted bracket load
- 2 Permitted bracket load in kN without man load
- Load curve with bracket lengths in mm