Technical data sheet

Device installation trunking Rapid 80, trunking width 170, trunking height 70 Item no. 6274701





GK device installation trunking, made of lead-free PVC, suitable for installing directly on the wall or on wall panels. Fastening takes place using the perforation in the trunking. The GK device installation trunking possesses a C profile on the floor to accept a plastic partition. All the switch programmes with a support ring and support clamp design as well as Modul 45 installation devices can be installed in the accessory mounting boxes of series 71GD.... The system opening is 76.5 mm. On each trunking length, a coupling pair is pre-assembled on one side. The cover must be ordered separately.














Polyvinylchloride

Master data

Item no.	6274701
Туре	GK-70170CW
Description 1	Device installation trunking
Description 2	with base perforation
Dimension	70x170x2000
Colour	Cream
RAL number	9001
Material	Polyvinylchloride
Material symbol	PVC
Smallest sales unit (VG)	2 m
Weight	180,00 kg/100 m

Technical data



	·
Length	2.000,00 mm
Width	170,00 mm
Height	70,00 mm
Number of covers	1
Number of insertable partitions	1
Rear panel version (inner side)	Continuous C profile
Rectangular shape	
Base perforation	With base perforation
Halogen-free	
Cable retaining clip	
Trunking height	70,00 mm
Trunking height	170,00 mm
Duct connector	
Cover mounting type	Internal
Mounting perforation in base	
Cover width	76,5 mm
Cover width 2	0,00 mm
Cover width 3	0,00 mm
Cover supplied	
Protective film	
Symmetrical	\checkmark